## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade	mark: FOREVER LIGHT
--------------------------	---------------------

Supplier's address: R&D Department, Krakowska 119, 50-428 Wrocław Wrocław Dolnośląskie, PL

Model identifier: RT	V003577
----------------------	---------

Type	of I	ight	sour	ce:
IVDC	<b>v</b> ı .	15116	JUUI	···

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G9		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 00 h), rounded st integer	6	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	480 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	-
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	87
Outer dimen-	Height	60	Spectral power dis-	See image
sions without	Width	12	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	12	range 250 nm to 800 nm, at full-load	

parts and non-			
lighting con-			
trol parts, if			
any (millime-			
, ,			
tre)			
Claim of equivalent power <sup>(a)</sup>	_	If yes, equivalent	-
		power (W)	
		Chromaticity coordi-	0,307
		nates (x and y)	0,329
2	1 .	nates (x and y)	0,323
Parameters for LED and OLED lig	nt sources:		
R9 colour rendering index value	26	Survival factor	0,90
the lumen maintenance factor	0,96		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,57	Colour consistency	6
,	,	in McAdam ellipses	
Claims that an LED light source	_(b)	If yes then replace-	-
replaces a fluorescent light		ment claim (W)	
		ment claim (vv)	
source without integrated bal-			
last of a particular wattage.			
Flicker metric (Pst LM)	0,1	Stroboscopic effect	0,1
, ,		metric (SVM)	•

(a)'-': not applicable; (b)'-': not applicable;

