Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: FOREVER LIGHT

Supplier's address: R&D Department, Krakowska 119, 50-428 Wrocław Wrocław Dolnośląskie, PL

Model identifier: RTV003662

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	G4					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Parameter Value Parameter Value General product pro	Froduct parameters							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer2Energy efficiency classFUseful luminous flux (фuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)170 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), ex- pressed in W1,7Standby power (Psb), expressed in W-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set84Outer dimen-Height37Spectral power dis-See image	Parameter		Value	Parameter	Value			
mode(kWh/1000 h), rounded up to the nearest integerclassUseful luminous flux (duse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)170 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set3 000On-mode power (Pon), ex- pressed in W1,7Standby power (Psb), expressed in W and rounded to the sec- ond decimal-Networked standby power (Pnet) for CLS, expressed in W and rounded to the second dec- imal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set84Outer dimen-Height37Spectral power dis-See image	General product parameters:							
dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setOn-mode power (Pon), ex- pressed in W1,7Standby power (Psb), expressed in W and rounded to the sec- ond decimal-Networked standby power (Pnet) for CLS, expressed in W-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set84Outer dimen-Height37Spectral power dis-	mode (kWh/10	00 h), rounded	2		F			
pressed in Wexpressed in W and rounded to the sec- ond decimalNetworked standby power (Pnet) for CLS, expressed in W and rounded to the second dec- imal-Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set84Outer dimen-Height37Spectral power dis-	dicating if it refe a sphere (360 ^o)	ers to the flux in , in a wide cone		temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K,	3 000			
(P _{net}) for CLS, expressed in W and rounded to the second dec- imaldex, rounded to the nearest integer, or the range of CRI-val- ues that can be setOuter dimen-Height37Spectral power dis-		ver (P _{on}), ex-	1,7	expressed in W and rounded to the sec-	-			
	(P _{net}) for CLS, e and rounded to	expressed in W	-	dex, rounded to the nearest integer, or the range of CRI-val-	84			
	Outer dimen-	Height	37	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing controlWidth10tribution in the range 250 nm to 800 nm, at full-loadin last page	separate con- trol gear, light-			range 250 nm to 800	in last page			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15			
		Chromaticity coordi-	0,426			
		nates (x and y)	0,398			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	16	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-' : not applicable;

(b)_{'-'} : not applicable;

