## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's r	name or trade mark:	FOREVER LIGHT
--------------	---------------------	---------------

Supplier's address: R&D Department, Krakowska 119, 50-428 Wrocław Wrocław Dolnośląskie, PL

	:dan±:£:au.	DTV/002667
ivioaei	i identiller:	RTV003667

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G4		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
_ ·	nption in on- 00 h), rounded st integer	3	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power (P <sub>on</sub> ), expressed in W		3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	-
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	85
Outer dimen-	Height	44	Spectral power dis-	See image
sions without	Width	17	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	17	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	25
		Chromaticity coordi-	0,314
		nates (x and y)	0,335
Parameters for LED and OLED light sources:			
R9 colour rendering index value	17	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

